

H2O-US3

Standard Undersink Filter



Cleaning your water without crowding the counter



- Sealed construction unit with 25,000 gallon capacity
- KDF® / GAC filter media
- 5-stage filtration and purification system
- Installed under the sink, out of sight
- Connects to separate, chromed, long-reach faucet
- Includes easy-installation kit
- Available inline for direct connection to faucet
- Bacteriostatic media prevents bacteria growth (algae, fungi)
- Improves taste and color, eliminates odor
- Reduces most EPA-listed contaminants
- Includes prorated warranty

Installation kit includes 6 feet of tubing (1/4" outside diameter), saddle valve, long-reach faucet, fittings and adapters.



Max Capacity	25,000 gallons (94,635 liters)
Recommended Flow	1.0 gpm (3.79 lpm)
Unit Height	16.5" (41.9 cm)
Unit Width	4" diameter (10.2 cm)
Unit Box Dimensions	18" x 7" x 6" (44.5 x 16.5 x 14.6 cm)
Unit Shipping Weight	7.5 lbs (3.4 kg)
Packing	8 per master case
Master Dimensions	21" x 18" x 13" (53.3 x 45.8 x 33 cm)
Master Case Weight	44.4 lbs (20.1 kg)

H₂O International Inc.
 3001 SW 15th St. - Suite C
 Deerfield Beach, FL 33442
 1 800 570-3464 USA Toll Free
 1 954 570-3464 International
 info@h2ofilter.com
 www.h2ofilter.com

