H2O-US4-13

Standard Undersink Filter with In-Line Connection







- Sealed construction unit with 25,000 gallon capacity
- KDF® / GAC Filter Media
- 5 stage filtration and purification system
- Installed under the sink, out of sight
- Includes quick-connect fittings and easy-installation kit
- Bacteriostatic media: prevents bacteria growth (algae, fungi)
- Improves taste and color, eliminates odor
- Reduces most EPA-listed contaminants
- Includes prorated warranty

Installation kit includes 6 feet of tubing (3/8" outside diameter), saddle valve, long-reach faucet, fittings and adapters.



Max Capacity	25,000 gallons (132,489 liters) 1.0
Recommended Flow	to 2.0 gpm (3.79 to 7.57 lpm)
Unit Height	16.5" (41.9 cm)
Unit Width	5" diameter (12.7 cm)
Unit Box Dimensions	18" x 7" x 6" (44.5 x 16.5 x 14.6 cm)
Unit Shipping Weight	10.4 lbs (4.72 kg)
Packing	6 per master case
Master Dimensions	21" x 18" x 13" (53.3 x 45.7 x 33 cm)
Master Case Weight	64.0 lbs (29 kg)

H₂O International Inc.

3001 SW 15th St. - Suite C Deerfield Beach, FL 33442 1 800 570-3464 USA Toll Free 1 954 570-3464 International info@h2ofilter.com www.h2ofilter.com



